

NEW! New Holland BOOMER™ Compact Tractors with SuperSuite™ Cab

TC40DA TC45DA



Now you can take comfort to the next level with a factory-installed SuperSuite™ cab available on New Holland models TC40DA and TC45DA Boomer™ compact tractors. The cab's innovative design provides the most comfortable environment available in a compact tractor cab, keeping the operator protected from all types of weather and removed from dust and noise. The cab's unique roof profile also keeps the overall height low, allowing the tractor to clear an 8-foot opening.

Visibility that can't be matched

No other compact tractor cab can beat the kind of all-direction visibility offered by the SuperSuite cab. The SuperSuite cab features a high-visibility roof panel. This "skylight" allows you to see the loader tool through a full range of operation for increased productivity.

More space and more comfort

With a spacious 60 ft³ of interior space, the SuperSuite cab provides a roomy work area. Two

large doors and a wide 16.5-inch entry threshold makes it easy to enter and exit. Step inside the cab and you'll be pleased to find generous hip, leg and head room. The adjustable, deluxe cloth-covered seat enhances the experience and makes it easy for any operator to find the perfect position. You'll also be impressed with how quiet the cab is.

Deluxe features are standard

The new SuperSuite cab comes equipped with a long list of features as standard equipment to make it the best value.

- High-visibility roof panel
- Heat and air conditioning
- Radio-ready with antenna and speakers
- Dual external mirrors
- Front and Rear cab-mounted work lights
- Front windshield washer / wiper

New Holland Boomer Compact Tractors with Cab Specifications

Model	TC40DA	TC45DA
Engine		
Gross HP (kW) @ rated speed	40 (29.8) @ 2600 rpm	45 (33.6) @ 2600 rpm
PTO HP (kW) @ rated speed	33.2 (24.8) @ 2600 rpm	37.8 (28.2) @ 2600 rpm
# of cylinders	4	4
Displacement, cu. in. (L)	121.7 (2.0)	135.2 (2.2)
Fuel Tank Capacity, US gal (L)	13 (49.2)	13 (49.2)
Alternator	55 amp	55 amp
Transmission		
	2 - range Hydrostatic with DualPower™ High/Low electronic shift in each range	
PTO		
Type	Independent	Independent
Standard Rear	540 rpm	540 rpm
Optional Mid	2000 rpm	2000 rpm
Hydraulics		
Implement pump flow, GPM (L/min)	9.8 (37.1)	9.8 (37.1)
Steering pump flow, GPM (L/min)	5.1(19.4)	5.1 (19.4)
3 Point Hitch		
Hitch type	Category I	Category I
Lift capacity @ 24" behind link ends, lbs (kg)	2330 (1057)	2330 (1057)
Axle Options		
Four Wheel Drive (FWD)	Standard	Standard
SuperSteer™ with Sensitrak™ Auto Four Wheel Drive*	Optional	Optional
Dimensions (Standard FWD, R4 tires)		
Wheelbase, in. (mm)	73.5 (1867)	73.5 (1867)
Overall length with 3 Point Hitch horizontal, in. (mm)	125.2 (3180)	125.2 (3180)
Minimum overall width @ rear axle, in. (mm)	68.3 (1735)	68.3 (1735)
Height to top of cab, in. (mm)	90.1 (2288)	90.1 (2288)
Approximate ship weight, lbs (kg)	4026 (1826)	4115 (1866)

Additional Standard Equipment – Cab

- 2 wide opening doors with grab rails and gas strut assist
- Rear opening window
- Deluxe cloth covered seat with weight adjustable suspension and swivel
- Tilt and Telescopic steering column
- Interior rearview mirror
- 2-pedal controls for hydrostatic transmission
- Suspended brake pedals
- Accessory power socket
- Cloth covered headliner
- Adjustable sun visor
- Single cab air filter
- Horn
- Left and right side steps
- Removable plug in rear of cab to route harness
- Cruise Control
- Cup Holder
- Toolbox
- Cell phone clip

Optional Equipment

- Rear window wiper and washer kit
- Beacon light and mounting kit
- High visibility panel guard for cab roof



YOUR NEW HOLLAND DEALER

Visit our Web site at www.newholland.com/na Or, call toll-free: **1-888-290-7377**



Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2006 CNH America LLC
New Holland is a registered trademark of CNH America LLC.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

NH6220604 • 080650 • TZ • PRINTED IN U.S.A.