New Holland 700 Series Rotary Cutters Standard-duty Models



736GC 737GC 738GC



Cut through the tough stuff on your property with a New Holland 700 Series standard-duty rotary cutter. You won't find a more reliable rotary cutter that delivers greater performance in tall grass, thick weeds and medium to heavy brush than a new 700 Series standard-duty model.

60", 72" and 84" cutting widths

Available in three models with 60", 72" and 84" cutting widths, 700 Series rotary cutters are built with heavier decks, stronger gearboxes and greater cutting capacity for dependably maintaining larger acreages. Designed for use with compact and utility tractors from 30 to 65 maximum horsepower, their productivity matches with the popular line of New Holland BoomerTM Compact and Utility tractors.

Long-life, worry-free performance

There's nothing standard about 700 Series standard-duty cutters. Rugged design features deliver exceptional durability and reliability:

- Larger discharge area improves cutting and overall performance
- Heavy-duty A-frame and stump/debris jumper ensure long life
- Smooth, rounded rear deck assists material cut and flow
- 3/8" x 3 or 1/2" x 4" heavy-duty high vacuum blades mow cleanly and smoothly
- 3/16" deck ring adds protection
- Bolt-on skid plates are counter-sunk won't catch on debris
- Extra heavy-duty, four-plate slip clutch and flexible top link add protection
- 65-hp gearbox rating with 5-year warranty (limited to defects in workmanship/material)

New Holland 700 Series Rotary Cutter Specifications – Standard-duty

MODEL:	736GC	737GC	738GC
	60"	72"	84"
Tractor HP (max.)	60 HP	65 HP	65 HP
Cutting Width	60"	72"	84"
Overall Width	65"	75"	90"
Overall Length	100"	106"	122"
Hitch	3-point	3-point	3-point
Driveline Category	Cat. I	Cat. I	Cat. I
Gearbox Rating (HP)	65 HP	65 HP	65 HP
Gearbox Warranty	3 Years	3 Years	3 Years
Slip Protection	Slip Clutch	Slip Clutch	Slip Clutch
Deck Gauge	7 Gauge	7 Gauge	7 Gauge
Side Panel Depth	8" x 7 Gauge	8" x 7 Gauge	8" x 7 Gauge
Blade Carrier	Pan	Pan	Pan
Output Shaft Diameter	2"	2"	2"
Blade Size	3/8" x 3" Updraft	1/2" x 4" Updraft	1/2" x 4" Updraft
Blade Tip Speed (540)	16,519 fpm	14,995 fpm	17,300 fpm
Cutting Height (min.)	2 inch	2 inch	2 inch
Tire & Wheel	Laminated	Laminated	Laminated
Safety Deflectors	Rubber Belting	Rubber Belting	Rubber Belting
Weight (lbs)	757	903	1065



YOUR NEW HOLLAND DEALER



Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.